Alaska Scientific Crime Detection Laboratory

DataMaster Evaluation Form Issued: 05/15/2020 Version: DMEF 2020 R0 Effective: 05/15/2020 Status: Active Start Date: 04/2//21 Analysts: <u>Dercu Watton</u> leturbished by factory for, repaired for blank errors on Calibration Reason for instrument evaluation Visual Inspection Clean Replace missing screws Cermetex Box is secure Ensure modem cable present Gas Valve upright or secured to wall All tubing and connections are secure O-ring inspection and ensure 2 O-rings in replacement bag Troubleshooting/Repair Mirror blucks taped, source block is tight, Fitter wheel assembly feels appropriate, controller board modification present, 5 way valve feels Uh. VOC (attached) Internal Standard value ≤ 3.00% No Verify software version Return to Factory for Repair Ready for Calibration Ready for Certification Proceed to Close Out End Date: _04/22/21 Page 1 of 1 All printed copies are uncontrolled. Approved by Chemistry Supervisor

VERIFICATION OF CALIBRATION REPORT

of DataMaster dmt Breath Test Instrument State of Alaska

Serial #: 100699 Scientific Crime Detection Laboratory - Statewide Breath Alcohol Program

Date:04/22/2021

External Standard Test Values	Diagnostic Check	
	VERSIONS DMT: 3.02 PIC: 3.03 Modem: 2.6 Questions: 2.2	
	TEMPERATURES	
	Sample Chamber = 48.7°C (44.0°C - 52.0°C)	PASSED
	Breath Tube = 45.0°C (38.0°C - 50.0°C)	PASSED
	SETTINGS Lamp Voltage = 1.56 V (0.95 V - 2.23 V)	PASSED
	Cooler Voltage = 1.56 V (0.95 V - 2.23 V)	PASSED
	Bias Voltage = 80 V (48 V - 112 V)	PASSED
	Chopper Freq = 533 Hz (475 Hz - 575 Hz) Barometer = 29.9 in	PASSED
	PUMP INFO Flow Rate = 4.862 L/M (3.500 L/M - 6.500 L/M)	PASSED
	DETECTOR INFO PUMP ON (0.003 V <= 0.010 V)	PASSED
	PUMP OFF (0.001 V <= 0.010 V)	PASSED
	FILTER INFO Filter 1 Filter 2 Filter 3	PASSED PASSED PASSED
	INTERNAL STANDARD	FAILED
	$Xq = 0.081 \underbrace{6.25\$}_{0.00\$} (0.00\$ - 4.00\$)$	

Diagnostic Check Failed