

Calibration complies with ISO/IEC 17025, ANSI/NCSL Z540-1, and 9001



Cert. No.: 6530-11569963

Traceable® Certificate of Calibration for Digital Barometer

Manufactured for and distributed by: VWR International LLC Radnor Corporate Center, Bldg 1,Ste 200, 100 Matsonford Road, Radnor, PA, 19087

Instrument Identification:

Model: 10510-922.

S/N: 200573788

Manufacturer: Control Company

Standards/Equipment:

do/Equipmont.					
<u>Description</u>	Serial Number	Due Date	NIST Traceable Reference		
Digital Barometer	D4540001	01 Nov 2020	1000447551		
Digital Thermometer	130070752	10 Mar 2021	4000-11170557		
Chilled Mirror Hygrometer	44654/2H3737	25 Nov 2021	17811		
Climate Chamber	W613.0046				

Certificate Information:

Technician: 57

Procedure: CAL-31

Cal Date: 24 Sep 2020

Cal Due Date: 24 Sep 2022

Test Conditions: 46.04%RH 23.41°C 1011mBar

Calibration Data: (New Instrument)

Unit(s)	Nominal	As Found	In Tol	Nominal	As Left	In Tol	Min	Max	±U	TUR
%RH	N.A.	N.A.		50.97	53	Y	48	54	0.74	>4:1
°C	N.A.	N.A.		25.25	25.1	Y	24.85	25.65	0.05	>4:1
mb/hPa	N.A.	N.A.		805.70	806	Y	802	810	0.62	>4:1
mb/hPa	N.A.	N.A.		909.86	910	Y	906	914	0.62	>4:1
mb/hPa	N.A.	N.A.		1017.80	1018	Y	1014	1022	0.62	>4:1

This certificate indicates Traceability to standards provided by (NIST) National Institute of Standards and Technology and/or a National Standards Laboratory.

A Test Uncertainty Ratio of at least 4:1 is maintained unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under test and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement: (GUM). The uncertainty represents an expanded uncertainty using a coverage factor k=2 to approximate a 95% confidence level. In tolerance conditions are based on test results falling within specified limits with no reduction by the uncertainty of the measurement. The results contained herein relate only to the item calibrated. This certificate shall not be reproduced except in full, without written approval of Control Company.

Nominal=Standard's Reading; As Left=Instrument's Reading; In Tol=In Tolerance; Min/Max=Acceptance Range; ± U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Ratio; Accuracy=±(Max-Min)/2; Min=As Left Nominal(Rounded) – Tolerance; Max= As Left Nominal(Rounded) + Tolerance;

Rid Rodriguez

Nicol Rodriguez, Quality Manager

Note:

Maintaining Accuracy:

In our opinion once calibrated your Digital Barometer should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Digital Barometer change little, if any at all, but can be affected by aging, temperature, shock, and contamination.

Recalibration:

For factory calibration and re-certification traceable to National Institute of Standards and Technology contact Control Company.

Issue Date: 24 Sep 2020

CONTROL COMPANY 12554 Galveston RD Suite B230 Webster TX USA 77598 Phone 281 482-1714 Fax 281 482-9448 sales@control3.com www.traceable.com

Control Company is an ISO/IEC 17025:2017 Calibration Laboratory Accredited by (A2LA) American Association for Laboratory Accreditation, Certificate No. 1750.01.

Control Company is ISO 9001:2015 Quality Certified by DNV GL, Certificate No. CERT-01805-2006-AQ-HOU-ANAB.

International Laboratory Accreditation Cooperation - Multilateral Recognition Arrangement (ILAC-MRA).